

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Withdrawn): A member for guiding and supporting at least one elongated flexible member, said guiding and supporting member comprising first and second outer side faces; at least one aperture extending between said first and second outer side faces, said aperture being defined by an uninterrupted inner circumferential surface extending from said first outer side face to said second outer side face and forming a passageway for receiving the at least one elongated flexible member within the guiding and supporting member, said inner circumferential surface being formed integral with said outer side faces and being convexly curved in a direction of the center of the aperture; and at least one elongated foot extending along a first portion of an outer sidewall for orienting and positioning the member on a structure.

Claims 2-7 (Cancelled).

Claim 8. (Withdrawn) The guiding and supporting member of claim 1 wherein the at least one aperture includes at least two apertures.

Claim 9. (Withdrawn) The guiding and supporting member of claim 8 wherein said at least two apertures include three apertures.

Claim 10. (Withdrawn) The guiding and supporting member of claim 8 wherein said at least two apertures include four apertures.

Claims 11-17 (Cancelled).

Claim 18. (Currently Amended) A guiding and supporting member for maintaining a flexible member at a predetermined minimum bend radius, said guiding and supporting member comprising a curved elongated body having a substantially fixed, predetermined bend between

first and second ends, the first end including a collar comprising a first circumferential flange, a second circumferential flange and a seat extending between said flanges.

Claim 19. (Original) The guiding and supporting member of claim 18 wherein said flanges and seat are sized for cooperating with an opening in a wiring guide to prevent said guiding and supporting member from moving along the flexible member relative to the wiring guide.

Claim 20. (Previously Presented) The guiding and supporting member of claim 18 further comprising a central passageway for receiving and supporting the elongated flexible member, said passageway including at least one inner surface for supporting the elongated flexible member when positioned within the guiding and supporting member.

Claim 21. (Previously Presented) The guiding and supporting member of claim 18 wherein said predetermined bend maintains said guiding and supporting member at a predetermined bend radius.

Claim 22. (Original) The guiding and supporting member of claim 18 wherein said elongated body is open at said first end and at a second end for receiving the elongated member, said second end including a second collar comprising first and second flanges and a seat extending between the first and second flanges of the second end.

Claim 23. (Withdrawn) The guiding and supporting member of claim 22 further comprising a third collar that is spaced from the first and second ends of said elongated body for providing an

attachment position at a location spaced along said elongated body between said first and second ends.

Claim 24. (Previously Presented) A guiding and supporting member for maintaining a flexible member at a predetermined minimum bend radius, said guiding and supporting member comprising an elongated body including a sweep having a first end, a second end and at least one roller positioned between said first and second ends, the first end comprises a collar comprising a first circumferential flange, a second circumferential flange and a seat extending between said flanges.

Claim 25. (Previously Presented) The guiding and supporting member of claim 24 wherein said elongated body includes a plurality of rollers spaced between said first and second ends.

Claim 26. (Withdrawn) The guiding and supporting member of claim 18 comprising a cradle that includes a collar spaced from the first and second ends of said elongated body for providing a hanger attachment position at a location spaced along said elongated body between said first and second ends.

Claim 27. (Original) The guiding and supporting member of claim 18 wherein said elongated body is substantially straight such that the predetermined bend radius is about zero.

Claim 28. (Currently Amended) A sweep for being used with a guiding and supporting member to maintain a flexible member at a predetermined radius, said sweep comprising a curved elongated body having a substantially fixed, predetermined bend, a passageway and first and

second ends for being securely retained within an aperture of a respective guide, said first and second ends each including a collar having a first circumferential flange, a second circumferential flange and a seat extending between said flanges for removably receiving a portion of the respective guide.

Claim 29. (Previously Presented) A sweep for being used with a guiding and supporting member to maintain a flexible member at a predetermined radius, said sweep comprising an elongated body including a plurality of rollers spaced along its length, a passageway and first and second ends for being securely retained within an aperture of a respective guide, said first and second ends each including a collar having a first circumferential flange, a second circumferential flange and a seat extending between said flanges for removably receiving a portion of the respective guide.

Claim 30. (Withdrawn) The sweep of claim 28 further comprising a third collar spaced from the collars at said first and second ends.

Claims 31-44 (Cancelled).